



## HUANGHE CABLE GROUP

**XLPE Insulated Steel Tape Armoured YE Sheathed Flame Retardant Fire Resistant Low Smoke Halogen Free Control Cable (WDZN-KYJY22)**

Number of Core	Nominal section area (mm <sup>2</sup> )	No. & Dia. Of Wires (No./mm)	Overall Diameter of Cable (mm)	Approx. Weight (kg/km)
2	1.5	1/1.38	13.8	325
	1.5	7/0.52	14.2	351
	2.5	1/1.78	14.6	381
	2.5	7/0.68	15.2	395
	4	1/2.25	15.6	433
	4	7/0.85	16.2	449
	6	1/2.76	16.6	495
	6	7/1.04	17.3	516
3	1.5	1/1.38	14.4	360
	1.5	7/0.52	14.8	372
	2.5	1/1.78	15.2	423
	2.5	7/0.68	15.8	440
	4	1/2.25	16.2	492
	4	7/0.85	16.9	512
	6	1/2.76	17.3	590
	6	7/1.04	18.1	614
4	1.5	1/1.38	15.3	410
	1.5	7/0.52	15.7	427
	2.5	1/1.78	16.2	478
	2.5	7/0.68	16.8	497
	4	1/2.25	17.4	585
	4	7/0.85	18.1	608
	6	1/2.76	18.6	692
	6	7/1.04	19.5	720
5	1.5	1/1.38	16.2	462
	1.5	7/0.52	16.7	477
	2.5	1/1.78	17.3	539
	2.5	7/0.68	18.0	585
	4	1/2.25	18.6	668
	4	7/0.85	19.4	694
	6	1/2.76	20.4	822
	6	7/1.04	21.3	855
7	1.5	1/1.38	17.3	475
	1.5	7/0.52	17.8	494
	2.5	1/1.78	18.5	576
	2.5	7/0.68	19.2	608
	4	1/2.25	19.9	715
	4	7/0.85	20.8	747
	6	1/2.76	21.8	914
	6	7/1.04	22.9	954



## HUANGHE CABLE GROUP

**XLPE Insulated Steel Tape Armoured YE Sheathed Flame Retardant Fire Resistant Low Smoke Halogen Free Control Cable (WDZN-KYJY22)**

Number of Core	Nominal section area (mm <sup>2</sup> )	No. & Dia. Of Wires (No./mm)	Overall Diameter of Cable (mm)	Approx. Weight (kg/km)
8	1.5	1/1.38	18.3	532
	1.5	7/0.52	18.9	553
	2.5	1/1.78	19.6	646
	2.5	7/0.68	20.5	676
	4	1/2.25	21.2	808
	4	7/0.85	22.1	843
	6	1/2.76	23.2	1031
	6	7/1.04	24.4	1079
10	1.5	1/1.38	20.7	643
	1.5	7/0.52	21.8	692
	2.5	1/1.78	22.7	810
	2.5	7/0.68	23.7	848
	4	1/2.25	24.6	1015
	4	7/0.85	25.8	1060
	6	1/2.76	26.6	1263
	6	7/1.04	28.0	1324
12	1.5	1/1.38	21.2	679
	1.5	7/0.52	22.0	707
	2.5	1/1.78	23.3	870
	2.5	7/0.68	24.3	911
	4	1/2.25	25.2	1100
	4	7/0.85	26.5	1149
	6	1/2.76	27.3	1389
	6	7/1.04	28.8	1449
14	1.5	1/1.38	22.5	770
	1.5	7/0.52	23.3	802
	2.5	1/1.78	24.3	960
	2.5	7/0.68	25.4	1006
	4	1/2.25	26.3	1224
	4	7/0.85	27.7	1278
	6	1/2.76	28.6	1556
	6	7/1.04	30.2	1622
16	1.5	1/1.38	23.5	839
	1.5	7/0.52	24.3	874
	2.5	1/1.78	25.4	1053
	2.5	7/0.68	26.6	1103
19	1.5	1/2.25	24.5	933
	1.5	7/0.85	25.4	971
	2.5	1/2.76	26.5	1181
	2.5	7/1.04	27.8	1237



## HUANGHE CABLE GROUP

**XLPE Insulated Steel Tape Armoured YE Sheathed Flame Retardant Fire Resistant Low Smoke Halogen Free Control Cable (WDZN-KYJY22)**

Number of Core	Nominal section area (mm <sup>2</sup> )	No. & Dia. Of Wires (No./mm)	Overall Diameter of Cable (mm)	Approx. Weight (kg/km)
24	1.5	1/1.38	27.9	1128
	1.5	7/0.52	29.0	1175
	2.5	1/1.78	30.3	1439
	2.5	7/0.68	31.9	1507
27	1.5	1/2.25	28.4	1210
	1.5	7/0.85	29.6	1260
	2.5	1/2.76	30.9	1553
	2.5	7/1.04	32.5	1627
30	1.5	1/1.38	29.3	1299
	1.5	7/0.52	30.5	1354
	2.5	1/1.78	31.9	1677
	2.5	7/0.68	33.6	1781
37	1.5	1/2.25	31.3	1507
	1.5	7/0.85	32.6	1570
	2.5	1/2.76	35.9	2340
	2.5	7/1.04	37.8	2453

Besides above lists, we can also provide other sizes depend on your requirements.